

KDT900

Mini Kiosk



The AML KDT900 is a full-featured, general purpose mini kiosk with a wide variety of application possibilities. Powered by Windows® Embedded CE 6.0, and featuring a number of user input/output options, the KDT900 is perfect for a contemporary time-and-attendance terminal, a retail price checking kiosk, an access control device, a digital sign, or a general purpose kiosk designed to put information at the fingertips of the customer.



In any application, the full VGA color display will impress with crisp, clear images, and built-in Power-over-Ethernet will ease installation and save money. Of course, an 802.11b/g/n radio is available for wireless installations, and multiple USB and RS-232 ports provide a host of options for peripheral devices if needed. To further round out the KDT900, users may choose to add any one of 1D laser, CCD, 2D barcode scanner, or an External Omni-directional laser and a magnetic stripe reader (MSR) and HID proximity card reader.

The KDT900 has many available integrated and external, user input options including a Magnetic-Stripe Reader and an External Omni-directional laser.



HID Proximity Card Reader Attachment



External Omni-directional Laser Attachment



Magnetic Stripe Reader Attachment



RAM® Mount Attachment



Applications

Time & Attendance General Purpose Kiosk
Digital Signage Price Checking
Access Control In-Store Stock Lookup

Learn more at www.amltd.com

Features

5.6" Full VGA color display w/touchscreen

Wired or wireless network connectivity

Power-over-Ethernet ready

Use Barcode, Magnetic Stripe (MSR) or HID Proximity readers for user input

Multiple USB and RS-232 ports

User programmable I/O

Windows® Embedded CE 6.0 Operating System

Benefits

Display colorful, engaging images and provide the simplicity of finger-touch navigation via the touchscreen panel.

Connect to a LAN via Ethernet or use the optional 802.11b/g/n radio.

Power the device over the Ethernet connection and enjoy the freedom of not having to physically locate the device near an electrical outlet.

The KDT900 can be equipped with any combination of 1D or 2D type barcode readers, or magnetic stripe or HID proximity card readers.

Multiple ports mean multiple options for keypads, printers and other accessories.

Configure the four front-panel switches as hot keys or for navigation purposes. Internal relays and optically isolated inputs provide the ability to interface with external devices like beacons or door locks.

Use standard Windows embedded software tools including Microsoft Embedded Visual C++ and Visual Studio to develop custom applications for the KDT900. For managed, cross platform software development, the KDT900 fully supports the .NET Compact Framework.

General Specs

Dimensions	14.6 cm L x 16.8 cm W x 5.0 cm D; 5.750" L x 6.625" W x 2.000" D
Weight	.81 lbs / 363g
Display	5.6" VGA (640x480), 16-bit Color TFT LCD
Touchscreen	Integrated resistive touch panel
Power Supply	Power-over-Ethernet (802.3af compliant); 12V DC 2.1 mm barrel jack
Internal UPS Battery	Optional 7.4V 2-Cell 2200 mAh Lithium-ion, ~2 hours runtime
Keypad	Four integrated momentary push buttons
I/O Ports	Three USB 1.1 full speed host ports; two RS-232 (one RJ-45, one expansion header); one Wiegand interface (header); two isolated digital inputs (screw terminal block); two isolated micro-relay outputs (screw terminal block); two internal bar code decoder connector (12 & 14 Pin FPC flex)
Networking	10/100Base-TX fast Ethernet; 802.11b/g/n wireless radio (optional internal USB type)
Audio	Integrated speaker and amplifier (tonal)
Color	Black; optional custom colors available for enterprise-wide installations (call for details)
Bar Code Scanner (optional)	Integrated linear CCD; integrated omni-directional 2D imager; integrated 1D laser; external omni-directional laser
Card Readers (optional)	Magnetic stripe reader; HID® ProxPoint® proximity card reader

Performance Specs

Processor	Samsung S3C2410 @ 202 MHz
Architecture	32-bit RISC ARM9 with AMBA (Advanced Microcontroller Bus Architecture)
Memory (RAM)	64 MB 100MHz SDRAM
Memory (Flash storage)	1024 MB (1 GB) Flash Storage; 16 MB ROM (OS)
Memory Expansion	SD Card Slot
Operating System	Windows® Embedded CE 6.0

Environmental Specs

Operating Temp	-20° to 50° C / -4° to 122° F
Storage Temp	-30° to 60° C / -22° to 140° F
Humidity	0% to 90% RH, non-condensing
Electrostatic Discharge	15kVDC through air; 8kVDC contact
Sealing	IP54; NEMA 12

Software Specs

Web Browser	Internet Explorer® 6 for Windows® CE
Diagnostic Tools	Standard suite of network and system diagnostic tools

Wireless Radio Specs (optional)

Radio	IEEE 802.11n Draft v2.0; IEEE 802.11b; IEEE 802.11g
Frequency	2.4 GHz Range
Signal Rates	11n (40MHz): up to 300Mbps 11n (20MHz): up to 144Mbps 11g: up to 54Mbps 11b: up to 11Mbps
Output Power	802.11b: 17± 1dBm 802.11g: 17± 1dBm 802.11n: 15± 1dBm
Antenna Configuration	1T2R Internal Antenna (1 Transmit / 2 Receiving)
Receive Sensitivity	802.11g: -70dBm @54Mbps 802.11b: -83dBm @11Mbps 802.11n: -83dBm @11Mbps
Security	None 64/128 Bit WEP WPA/WPA2 Personal (PSK) WPA/WPA2 Enterprise (EAP) 802.1x Authentication Supplicants

Mounting & Accessories (optional)

Mounting Kits	Pole or post mount kit; angled wall mount kit; Adjustable universal RAM Mount™ kit
Peripheral Kits	Top-mount MSR kit; Side-mount HID® ProxPoint Plus® kit

Regulatory Specs

Certifications	FCC Part 15 Class A
Environmental	RoHS, Pb-Free

Maintenance & Support

Standard Warranty	One year standard warranty agreement
Optional	Extended Warranty Plus (3 years); Extended Warranty (3 years); CARE Plan Extended Warranty (3 years)



Specifications are subject to change without notice.
All names and products are the trademarks or registered trademarks of their respective organizations.
Windows is a registered trademark of Microsoft Corporation in the United States and other countries.



Corporate Headquarters
2190 Regal Parkway
Euless, Texas 76040

Sales & Customer Service
Tel: 800-648-4452
Fax: 817-685-6232
Email: sales@amltd.com

www.amltd.com
www.amlkiosks.com
Local: 817-571-9015
Fax: 817-571-6176

Technical Support
Tel: 877-842-3990
Fax: 817-685-6232
Email: support@amltd.com



© 2011 American Microsystems, Ltd.

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684