



Coffee & Tea Shop



Retail



Healthcare & Pharmacy



Post & Parcel

SPECIALIZED SOLUTION!

2 inch Barcode Label Printer **SLP-DX220**



Peeler



Standard



Auto-cutter

Advanced Performance

- Printing speed up to 6 ips (152 mm/s)
- Fast data processing speed of various types of label

Smart Media Detection™

- Automatic paper detection such as gap media, black mark media and short length media paper



BIXOLON®
a Better Solution for your Business™

2 inch Barcode Label Printer

SLP-DX220



Standard

Peeler

Auto-cutter

FEATURES

Dual interface

- Standard:
USB + Serial
- Optional:
USB + Ethernet + WLAN*



User-friendly Design

- Easy paper loading with adjustable paper guide
- Pause and cancel function-keys



Powerful Compatibility

The SLP-DX220 is fully compatible with market-leading programming language; SLCS, BPL-Z™, BPL-E™.



Label Artist™

Bixolon provides its custom label design program as bundle. It supports **database** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

BR-SLP-DX220-EN-MAR14

Copyright © 2014 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

SPECIFICATIONS

Printer Specifications

Print Method: Direct Thermal

Print Speed: SLP-DX220: Up to 6 ips (152 mm/s) / SLP-DX223: Up to 4 ips (100 mm/s)

Print Resolution: SLP-DX220: 203 dpi / SLP-DX223: 300 dpi

Print Width: SLP-DX220: Up to 54 mm / SLP-DX223: Up to 56.9 mm

Print Length: 6 ~ 2000 mm

Media Sensor: Transmissive, Reflective (adjustable), Head open

Media Characteristics

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold

Media Width: 15 ~ 60 mm

Media Roll Diameter: Up to 130 mm

Media Thickness: 0.06 ~ 0.20 mm

Supply Method: Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H): 120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)

Weight: 1.36 kg (2.99 lbs.)

Power: EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory: 64MB SDRAM, 128MB Flash

Interface: Dual Interface

Standard: USB V2.0 HS + Serial

Optional: USB V2.0 HS + Ethernet + WLAN*

* WLAN: 802.11b/g/n USB dongle type (optional)

Environment Characteristics

Temperature: Operating: 0~40°C (32~104°F)

Storage: -20~60°C (-4~140°F)

Humidity: Operating: 10 ~ 80% RH

Storage 10 ~ 90% RH

Software

Emulation: SLCS, BPL-Z™, BPL-E™

Driver/Utility: Windows Driver (Euro Plus/Seagull), OPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB / Ethernet Driver, Utility Program, Label Artist™

SDK: Android SDK

Fonts / Graphics / Symbolologies

Character Sets: · 10 SLCS Resident Bitmap Fonts

· One SLCS Resident Scalable Font

· 16 BPL-Z™ Resident Bitmap Fonts

· One BPL-Z™ Resident Bitmap Font

· 5 BPL-E™ Resident Bitmap Fonts

· 23 Code Page

· Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbolologies: 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39

Options

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock)

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

7-8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de



Coffee & Tea Shop



Retail



Healthcare & Pharmacy



Post & Parcel

SPECIALIZED SOLUTION!

2 inch Barcode Label Printer **SLP-DX220**



Peeler



Standard



Auto-cutter

Advanced Performance

- Printing speed up to 6 ips (152 mm/s)
- Fast data processing speed of various types of label

Smart Media Detection™

- Automatic paper detection such as gap media, black mark media and short length media paper



BIXOLON[®]
a Better Solution for your Business™

2 inch Barcode Label Printer

SLP-DX220



Standard

Peeler

Auto-cutter

FEATURES

Dual interface

- Standard:
USB + Serial
- Optional:
USB + Ethernet + WLAN*



User-friendly Design

- Easy paper loading with adjustable paper guide
- Pause and cancel function-keys




function-keys



Powerful Compatibility

The SLP-DX220 is fully compatible with market-leading programming language; SLCS, BPL-Z™, BPL-E™.



BPL-Z™

BPL-E™

Label Artist™

Bixolon provides its custom label design program as bundle. It supports **database** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

BR-SLP-DX220-EN-MAR14

Copyright © 2014 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

SPECIFICATIONS

Printer Specifications

Print Method: Direct Thermal

Print Speed: SLP-DX220: Up to 6 ips (152 mm/s) / SLP-DX223: Up to 4 ips (100 mm/s)

Print Resolution: SLP-DX220: 203 dpi / SLP-DX223: 300 dpi

Print Width: SLP-DX220: Up to 54 mm / SLP-DX223: Up to 56.9 mm

Print Length: 6 ~ 2000 mm

Media Sensor: Transmissive, Reflective (adjustable), Head open

Media Characteristics

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold

Media Width: 15 ~ 60 mm

Media Roll Diameter: Up to 130 mm

Media Thickness: 0.06 ~ 0.20 mm

Supply Method: Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H): 120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)

Weight: 1.36 kg (2.99 lbs.)

Power: EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory: 64MB SDRAM, 128MB Flash

Interface: Dual Interface

Standard: USB V2.0 HS + Serial

Optional: USB V2.0 HS + Ethernet + WLAN*

* WLAN: 802.11b/g/n USB dongle type (optional)

Environment Characteristics

Temperature: Operating: 0~40°C (32~104°F)

Storage: -20~60°C (-4~140°F)

Humidity: Operating: 10 ~ 80% RH

Storage 10 ~ 90% RH

Software

Emulation: SLCS, BPL-Z™, BPL-E™

Driver/Utility: Windows Driver (Euro Plus/Seagull), OPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB / Ethernet Driver, Utility Program, Label Artist™

SDK: Android SDK

Fonts / Graphics / Symbolologies

Character Sets: · 10 SLCS Resident Bitmap Fonts

· One SLCS Resident Scalable Font

· 16 BPL-Z™ Resident Bitmap Fonts

· One BPL-Z™ Resident Bitmap Font

· 5 BPL-E™ Resident Bitmap Fonts

· 23 Code Page

· Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbolologies: 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39

Options

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock)

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

7-8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684