

- Strong, all-metal construction and superior throughput for harsh industrial environments
- Compact size fits spaceconstrained applications
- Smart Printing capabilities support stand-alone printer applications, eliminating PC expense and complexity
- All-in-one, user-selectable printer languages – Fingerprint/Direct Protocol (DP), IPL, ZSim and DSim – in every printer
- Secure wireless connectivity:
   CCX and WiFi® certified with WPA2
- Integrated Ethernet, USB host and device, and serial interface standard
- Internet Protocol v6 (IPv6) support

A member of the smartest bar code printer family on the market, the PF2i is flexible and programmable, enabling customers to optimize their printing operations, streamline deployment, and achieve quick return on investment. Built to meet the needs of mission-critical applications, the rugged PF2i delivers advanced, secure connectivity and the latest network protocols, ensuring peace-of-mind today and a reliable, scalable solution for the long haul. The compact PF2i Mid-Range Printer is part of Intermec's complete line of smart, strong and secure industrial printers.

#### Smart

The PF2i's smart design features support increased productivity in demanding environments. As a Smart Printer, the PF2i can host stand-alone applications, developed through Intermec Fingerprint programming language, that reduce errors and streamline operational processes. Smart Printers can eliminate the PC and control other devices directly (such as scanners, scales, applicators), improving efficiency and decreasing infrastructure costs and complexity.

The PF2i's integrated device management and diagnostic capabilities, provided through Intermec SmartSystems™ and Wavelink Avalanche™, reduce downtime and simplify deployment. With its user-selectable, all-in-one programming languages (Fingerprint,

IPL, ZSim, DSim), the PF2i fits existing IT infrastructures, deploying with drop-in simplicity to Intermec or mixed printer environments. Its secure, industry-standard connectivity options support easy integration and fast deployment.

### Strong

Compact and rugged, the all-metal PF2i incorporates features that reduce downtime and minimize maintenance costs. Despite its small size, the PF2i can use a full size label roll (up to 8.4 in/213 mm), reducing the frequency of media changes.

Its enhanced self-strip option with unique tension control tooling delivers consistent performance across multiple media types. Replacing printheads is fast and easy, thanks to the magnetic QuickMount™ printhead design. The PF2i is co-engineered and tested with Intermec labels and other media products, ensuring optimized, superior performance when used with genuine Intermec media.

## Secure

Multiple interface options are available, including the highest level of secure wireless connectivity (WPA2). The industry's only printers available with WiFi- and CCX-Certification, Intermec industrial printers help maintain wireless network integrity and reduce configuration time. Every printer ships with Ethernet



connectivity, as well as with emerging network protocol IPv6, ensuring long-term, enterprise scalability. Other connectivity options – standard RS232 and USB ports, and optional parallel, double serial or industrial interfaces – provide additional integration flexibility.

The standard CompactFlash™ memory slot is complemented by new USB host and device support. Handy, inexpensive and PC-compatible, CompactFlash and USB memory technologies provide extra storage for Fingerprint programs, layouts, graphics\*, fonts and firmware upgrades.

\* Fingerprint only

#### Description

Direct thermal and thermal transfer label, ticket and tag printer.

#### **Physical Characteristics**

**Length:** 397 mm (15.6 in) **Height:** 178 mm (7 in)

Height (big top): 205 mm (8.1 in)

**Width:** 194 mm (7.6 in) **Weight:** 5.5 kg (12 lbs.)

#### **Print Specifications**

Max. Width: 56 mm (2.2 in)
Max. Length: 4095 mm (161.2 in)

#### **Print Speed**

100 - 200 mm/s (4 - 8 ips) variable

## **Print Resolution**

8 dots/mm (203 dpi)

#### Media

Type: Labels & Tags

Max/ Min Width: 60/25.4 mm (2.36/1 in)

Thickness: 3.0 to 7.5 mil

Configuration: Roll-fed or fanfold

Sensing: Gap, notch, black mark, continuous Label Roll Max Diameter (long door): 152.4 mm (6 in)

Label Roll Max Diameter (short door): 213 mm (8.38 in)

Label Roll Core: 38-76mm (1.5-3 in)

Type: Ribbons

Roll Max Diameter: 65 mm (2.56 in), approx. 225m

Core ID: 25.4 mm (1")
Type: Wax, mid-range, resin

Genuine Intermec Media: www.intermec.com/media

#### Interfaces

#### Standard:

- Ethernet 10/100 Mbps
- RS-232, up to 115.2 kB/s

#### **Supported Serial Protocols:**

- Fingerprint/Direct Protocol: XON/XOFF, ENQ/ACK, DTR, RTS/CTS
- IPL: XON/XOFF, Intermec Std. Protocol
- USB 2.0

#### Optional:

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

#### Wireless:

- IEEE 802.11 b/g
- Wi-Fi Certified, CCX (Cisco®) version 3 Certified
- WEP, WPA, WPA2, 802.11x (EAP-TTLS, LEAP, PEAP, FAST), 802.11i
- Multiple industrial antenna options for maximized coverage

#### Supported Protocols:

TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMPv3, SMTP.SNMP-MIB II supported (over UDP/IP), private enterprise MIB included Supports IPv4 and IPv6

#### Software

#### **Printer Command Languages:**

- IPL
- Fingerprint/Direct Protocol
- ZSim (ZPL)
- DSim (DPL)
- XML enabled for SAP® All and Oracle® WMS

#### Applications / Drivers:

- InterDriver™ Windows printer driver
- Intermec label design and print package
- PrintSet for printer configuration

#### Development Software:

• Intermec Fingerprint Application Builder™ (IFAB)

## Device Management Support:

- SmartSystems™
- Wavelink Avalanche"

#### **Bar Code Symbologies**

All major 1D and 2D symbologies are supported.

#### Fonts

Scalable fonts including CP1252 Font cache for maximum performance Non-Latin fonts and legacy fonts available

#### Graphics

Supports PCX file format. (Fingerprint Only)
Other formats supported with Label Generation Tools

#### Memory

**Standard:** 16MB Flash memory, 32MB SDRAM, 1 Compact Flash slot

**Available:** 1GB CompactFlash memory, multi-GB USB memory device (FAT16/FAT32 USB drivers supported)

### **Keypad Control Panel**

Interactive numeric keypad control panel

#### **Power Supply**

AC Voltage: 90 to 265 VAC, 45 to 65Hz PFC Regulation: IEC 61000-3-2

Power Consumption: Standby 15W; Peak 300W

#### **Operating Environment**

Ambient Operating Temperature:

+5°C to +40°C (+41°F to +104°F)

Storage Temperature: -20°C to +70°C (-4°F to +152°F)

Humidity: 20 to 80% non-condensing

#### **Regulatory Approvals**

CE (EN55022 Class A), FCC Class A, UL/cUL, C-Tick

#### Options

Integral self-strip unit with liner takeup, Label Taken Sensor (LTS), Compact Flash (CF) memory, various international double byte fonts, alphanumeric keyboard\*, parallel interface board, additional serial interface board\*, industrial interface board\*, applicator interface board\*, real time clock, media supply hub, label low sensor

\*Not applicable when using IPL firmware

#### North America Corporate Headquarters 6001 36th Avenue West

Everett, Washington 98203 Phone: (425) 348-2600 Fax: (425) 355-9551

#### North Latin America Headquarters Office

Phone: +52 55 52-41-48-00 Fax: +52 55 52-11-81-21

#### South Latin America Headquarters Office

Brazil Phone: +55 11 5502.6770 Fax: +55 11 5502.6780

#### Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom Phone: +44 118 923 0800 Fax: +44 118 923 0801

# Asia Pacific Headquarters Office Singapore

Phone: +65 6303 2100 Fax: +65 6303 2199

### Internet

www.intermec.com Worldwide Locations: www.intermec.com/locations

#### Sales

Toll Free NA: (800) 934-3163 Toll in NA: (425) 348-2726 Freephone ROW: 00 800 4488 8844 Toll ROW: +44 134 435 0296

## OEM Sales

Phone: (425) 348-2762

#### Media Sales

Phone: (513) 874-5882

#### Customer Service and Support

Toll Free NA: (800) 755-5505 Toll in NA: (425) 356-1799







Copyright © 2009 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611479-015 10/09

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



# **Legacy Technology Services**

## We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert

866-271-9891

## About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

## Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

## **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

## Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

## **Trade-in and Disposal services**

- That old equipment laying around your facility may still have some value.
   Legacy routinely purchases equipment from our clients around the globe.
  - · Data destruction
  - · Hardware disposal
  - Auditing services

### Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

## **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















