



GENERAL PURPOSE CORDLESS LINEAR IMAGER

MOTOROLA LI4278

THE NEXT GENERATION IN 1D SCANNING

The LI4278 takes 1D bar code scanning to the next level, allowing workers to scan faster and farther. Workers can capture virtually any 1D bar code - including the typical bar codes that are printed on paper labels; electronic bar codes displayed on the screen of a mobile phone, tablet or computer that allows retailers to easily process loyalty cards, mobile coupons and more; and the high density (HD) bar codes commonly used in electronic component manufacturing. 100 percent UPC bar codes can be captured from near contact to over 30 in./76.2 cm away, while 200% UPC codes can be scanned at 55 in./139.7 cm away. Since bar codes can be captured at extreme angles, scanning is easier than ever, so workers spend less time maneuvering the scanner and more time on task. And an optional cradle that enables presentation mode gives your workers the flexibility to use the scanner in handheld and hands-free modes.

CORDLESS FREEDOM

Bluetooth[®] frees workers from cords, allowing cashiers to easily scan items inside and outside of the cash wrap. In addition, Bluetooth v2.1 with EDR provides better encryption for improved security; better wireless performance; better energy management to preserve power for a full shift and easy pairing with the host device.

BUILT FOR ALL DAY EVERYDAY USE

A patent pending single circuit board improves reliability by eliminating interconnections. Superior battery power management delivers the largest number of scans per battery charge to support scan intensive applications. You can use it in dusty and wet environments. The scan line is easy to see outdoors in bright sunlight as well as indoors in dim lighting. It can survive drops to concrete. And both cradles can handle over a quarter million insertions.

COST EFFECTIVE UP GRADE PATH

The LI4278 provides a positive return on investment by utilizing the same existing cradles and accessories as its cousins, the LS4278 and DS6878. Current investments are preserved, yet you can easily migrate to the latest in scanning technology.

MAXIMUM UPTIME FOR A LOW TCO

Remote management tools combine with industry leading all-inclusive affordable service plans to keep devices in the hands of your workforce practically every minute of every working day, Service from the Start Advance Exchange Support provides next-business-day replacement of devices that require repair. Built-in Comprehensive Coverage protects your scanners from the unexpected, significantly reducing unforeseen repair expenses and delivering service peace of mind from the moment you purchase the device.

FEATURES

Excellent 1D scanning performance

Delivers superior scanning speed and a wide data capture range

Captures virtually all 1D bar codes on any surface — including mobile phone displays

Capture bar codes printed on traditional paper labels or displayed on the screen of a mobile phone, tablet or computer

Wide working range

Reads UPC bar codes from 1 in./2.54 cm to over 30 in./76.2 cm as well as high density codes and extended ranges for greater application flexibility

Superior motion and angular tolerance

Bar codes can be captured faster, and there is no need to pause between scans

Patent pending single circuit board construction

Maximizes durability and reduces downtime

Bright crisp aiming line

Easier to aim in bright or dim lighting environments

FOR MORE INFORMATION, VISIT WWW.MOTOROLASOLUTIONS.COM/LI4278 OR ACCESS OUR GLOBAL CONTACT DIRECTORY AT WWW.MOTOROLASOLUTIONS.COM/UK/CONTACTUS

SPECIFICATIONS CHART

PHYSICAL CHARACTERISTICS

| Dimensions | 3.84 in. H x 2.75 in. W x 7.34 in. L |
|------------------------|--|
| | 9.8 cm H x 7 cm W x 18.6 cm L |
| Weight | 7.9 oz./224 grams |
| Cradle Interface | RS232, RS485 (IBM), USB, Keyboard Wedge |
| Color | Black; White |
| Battery | Rechargeable replaceable battery with |
| | 'green sustainability' |
| PERFORMANCE CHAR | ACTERISTICS |
| Skew | Tolerance ±65° |
| Pitch | Tolerance ±65° |
| Roll | Tolerance ±45° |
| Scan Pattern | Single bright aiming line |
| Scan Angle | Horizontal 35° |
| Scan Speed | 547 scans per second |
| Motion Tolerance | 25 in./ 63.5 cm per second |
| Light Source | LED Class 1 device 617nm (amber) |
| Min. Print Contrast | 15% MRD |
| Scans Per Charge | Up to 57,000 |
| Hours of Operation | Per full charge: 72 hours |
| USER ENVIRONMENT | |
| Ambient Light Immunity | Max 108,000 lux |
| Operating Temp. | 32° F to 122° F/ 0° C to 50° C |
| Storage Temperature | -40° F to 158° F/-40° C to 70° C |
| Humidity | 5% to 85% RH, non-condensing |
| Drop Specification | Over 100 drops at 5 ft./1.5 m at room |
| | temperature; survives 6ft./1.8 m drops |
| | to concrete |
| Environmental Sealing | Gasket sealed housing withstands dust and |
| | can be sprayed clean |
| Bar Code Symbologies | UPC/EAN: UPC-A, UPC-E, UPC-E1, EAN-8/JAN |
| | 8, EAN-13/JAN 13, Bookland EAN, Bookland |
| | ISBN Format, UCC Coupon Extended Code, |
| | ISSN EAN Code 128 Including GS1-128, ISBT |
| | 128, ISBT Concatenation, Code 39 including |
| | Trioptic Code 39, Convert Code 39 to Code |
| | 32 (Italian Pharmacy Code), Code 39 Full |
| | ASCII Conversion Code 93 Code 11 Matrix |
| | 2 of 5 Interleaved 2 of 5 (ITF) Discrete 2 |
| | of 5 (DTF) Codabar (NW - 7) MSI Chinese |
| | 2 of 5 IATA Inverse 1D (except all GS1 |
| | DataBars) GS1 DataBar including GS1 |
| | DataBar-14, GS1 DataBar Limited, GS1 |
| | DataBar Expanded |

Part number: SS-LI4278. Printed in USA 12/11. MOTOROLA , MOTO , MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LL C and are used under license. All other trademarks are the property of their respective owners. ©2011 Motorola, Inc. All rights reserved.



WIRELESS CONNECTIVITY

| WINELESS CONNECTIVIT | I |
|---|---|
| Radio | Bluetooth v2.1 Class 2 Radio |
| Data Rate | 3.0 Mbit/s (2.1 Mbit/s) Bluetooth v2.1 |
| Radio Range | 330 ft./100 m (line of sight) |
| REGULATORY | |
| Technical | EMC FCC Part 15 Class B, ICES 003 Class B, |
| Requirements | IEC 60601-1-2 Environmental RoHS Directive |
| | 2002/95/EEC Electrical Safety C22.2 No. |
| | 60950-1, EN 60950-1, IEC 60950-1, UL 60950- |
| | 1 LED Class 1 |
| Environmental | RoHS Compliant |
| UTILITIES | |
| 123Scan, Remote Scanner Management (RSM), Scanner Management | |
| Services (SMS), Motorola Scanner SDK | |
| DECODE RANGES (TYPICAL WORKING RANGES *) | |
| 3 mil | 5-7 in./12.7-17.8 cm |
| 4 mil | 4-10 in./10.2-25.4 cm |
| 5 mil | 3-13 in./7.6-33 cm |
| 7.5 mil | 1.5 in19 in./ 3.8-48.3 cm |
| 13 mil (100% UPC-A) | 1-31 in./2.5-78.7 cm |
| 20 mil | 1-42 in./2.5-106.7 cm |
| 26 mil (200% UPC-A) | 3-55 in./7.6-140 cm |
| 100 mil (paper) | >20 ft./6 m |
| * Ranges are calculated on Code 39 unless otherwise noted | |
| WARRANTY | |
| Subject to the terms of Motorola's hardware warranty statement, | |
| the LI4278 is warranted against defects in workmanship and | |
| materials for a period of 36 months from the date of shipment. | |
| For the complete Meterale hardware product warranty statement | |

For the complete Motorola hardware product warranty statement, go to: http://www.motorola.com/warranty

Built-in rechargeable replaceable battery

Provides largest number of scans per charge — well beyond a single shift in the highest usage profiles; replaceable battery ensures long lifecyle

Long life industrial charging contacts

Reliable performance, rated to 250,000+ insertions

Compatible with 123Scan² and Remote **Scanner Management** (RSM)

Dramatically reduces management time and cost, from initial configuration to day-to-day management; SDK available for custom development

Withstands 100+ consecutive drops to concrete

Protects against downtime from breakage due to everyday drops

Multi point-to-point

Use up to three scanners with a single desktop cradle and seven scanners with a presentation cradle, reducing capital expenditures and maintenance costs

Batch mode operation

Allows user to continue scanning outside communications range; can scan over 500 UPC bar codes into memory and upload automatically when in communication range

Flexible mounting vertical or horizontal

Desktop cradle provides versatility to accommodate your unique environment

Bluetooth 2.1

Provides better security, better performance, better energy management and much easier pairing over the Bluetooth wireless connection

Backward compatible

Works with LS4278 cradles, providing a very costeffective upgrade path

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













