



MC70

Enterprise Digital Assistant



FEATURES

Industry-leading double impact testing (drop and tumble), IP54 sealing, integrated antennas

Lightweight yet rugged; built for year-round use in nearly any environment

Marvell's processor, designed for mobility: XScale PXA270 @ 624 MHz

Desktop-like multimedia performance with lower power requirements

Microsoft's Windows Mobile 5.0 Premium or Phone Edition, or Windows Mobile 6.1 Classic or Premium

Integrated multimedia, persistent memory

Integrated GPS via Autonomous SiRF III GPS positioning system

The optional integrated high-sensitivity GPS allows to track personnel and equipment and minimize transportation costs. Please refer to the MC70+GPS Specification Sheet for details.

The first rugged enterprise digital assistant

The flagship MC70 Enterprise Digital Assistant (EDA) is a rugged handheld mobile device that incorporates a mobile phone, PDA, computer, scanner and imager in a single unit designed for the rigors of all-day, everyday usage. This compact, lightweight device combines multi-mode wireless networking, voice and data communications, and advanced data capture in an enterprise productivity tool that can support nearly any application in any environment. Superior voice functionality includes outstanding acoustic performance and voice quality, handset, headset and speakerphone modes. Your mobile workers will have everything they need to increase productivity and efficiency inside and outside your four walls — from field workers reading meters and repairing equipment to drivers delivering packages, hospital workers checking lab results and medication orders, and more.

Rugged construction delivers a low TCO

The industry leading innovative mechanical design and technology platform offer superior construction and expandability, delivering outstanding investment protection and a low total cost of ownership (TCO). Engineered to withstand rigorous use in extreme environments and working conditions, the MC70, including the internal WLAN and external WWAN antennas, can endure multiple drops, a wide range of temperatures, moisture, dust, and more and still deliver reliable performance.

Built-in WWAN/WLAN/WPAN

The MC70 offers robust and cost-effective anytime, anywhere voice and data connectivity. For workers outside of your facility, support for GSM/EDGE and CDMA-EVDO networks delivers global coverage, fast wireless data speeds that enable rich applications, and enterprise level security. Inside your facility, the MC70 connects to your wireless LAN for voice and data communications, providing better control over wireless WAN usage — and costs. And wireless PAN functionality, via Bluetooth, further increases employee productivity through wireless printing and more.

Reduce the cost and complexity of mobility

The versatile, effective MC70 is a smart investment, providing a cell phone, PDA and more - all in a single rugged device. Capital expenditures and IT support costs are significantly reduced. Superior manageability enables you to easily and remotely provision, track and support all your MC70 devices from one central location through our Mobility Services Platform. A full suite of accessories provides maximum application flexibility. And when you purchase Service from the Start with Comprehensive Coverage, we will repair damaged displays, plastics, keyboards, circuit boards, and other internal and external components at no extra charge — helping you protect your investment and maintain peak performance. For more information on the MC70, visit us on the web at www.motorola.com/mc70

SPECIFICATION SHEET

MC70

MC70 Specifications

WWAN: GSM/EDGE and CDMA-EVDO Rev. 0 compatibility

Voice and high-speed wireless data

WLAN: 802.11a/b/g tri-mode radio; comprehensive VoIP support

Cost-effective voice and data connectivity in the office

WPAN: Bluetooth v1.2, Class II

Wireless modem, printing synchronization, and more

High quality speakerphone, microphone and transducer

Superior voice quality and performance

On-board advanced data capture: 1D and 2D bar code scanning from near contact to 55 in./139.7cm

Automate and error proof data collection and increase productivity

3.5 in. QVGA color screen

Easy to view in any lighting

Multiple keyboard options: QWERTY or numeric

Flexibility to meet diverse user and application needs

Support for standard SD and SDIO cards

Provides additional memory and expandable functionality

Multiple battery options: standard and extended

Ample power for full shifts in nearly any environment

Physical Characteristics

Dimensions:	6 in. L x 3.1 in. W x 1.5 in D 15.3 cm L x 7.6 cm W x 3.7 cm D CDMA/EVDO Rev. 0 configurations: 6 in. L x 3.1 in. W x 1.7 in. D 15.3 cm L x 7.9 cm W x 4.4 D
Weight (including standard battery):	LAN/PAN configs: 11.2 oz./314 g WAN/LAN/PAN configs: 12 oz./336 g CDMA/EVDO Rev. 0 configs: 14.1oz./400g
Display:	Transflective color 3.5" QVGA with backlight, TFT-LCD, 65K colors, 240 W x 320 L (QVGA size)
Touch Panel:	Glass analog resistive touch
Backlight:	LED backlight
Main Battery:	Rechargeable Lithium Ion 3.7V, 1900 mAh, 3600 mAh, 3800 mAh or 4800 mAh Smart Battery
Backup Battery:	Ni-MH battery (rechargeable) 20mAh 1.2V, 2 cells (not user-accessible)
Expansion Slot:	User accessible SDIO slot (with secure cover); accommodates extended cards (with cover removed); NOTE: terminals with extended cards cannot be accommodated in the charging cradle and will not be sealed
Network Connections:	Ethernet (via cradle); full-speed USB, host or client
Notification:	Vibrator and LED
Keypad Options:	26 Numeric key; 44 QWERTY key
Audio:	Speaker, receiver, microphone, headset jack, software support for full duplex record and playback (stereo)

Performance Characteristics

CPU:	XScale™ 624 Mhz processor
Operating System:	Microsoft® Windows™ Mobile 5.0 Premium, Microsoft® Windows™ Mobile 5.0 Phone Edition, Windows Mobile 6.1 Classic or Premium
Memory:	64MB RAM/128MB ROM or, 128MB RAM/128MB ROM
Interface:	RS-232, USB 1.1

User Environment

Operating Temp.:	14°F to 122° F/-10°C to 50° C
Storage Temp.:	-40° F to 140° F/-40° C to 60° C (w/o battery)
Humidity:	95% non-condensing
Drop Spec:	5 ft. drop to concrete, 2 drops per 6 sides at ambient temperature 73° F/23° C; 4 ft. drop to concrete, 6 drops per 6 sides over operating temperature range
Tumble Spec:	1,000 1.6 ft./1.5 m tumbles (2,000 drops)
Sealing:	IP54
Electrostatic Discharge (ESD):	±15kV air discharge, ±8kV direct discharge

Wireless WAN Data and Voice Communications

WWAN Radio:	GSM/EDGE (850, 900, 1800 and 1900 MHz) CDMA-EVDO Rev. 0
-------------	---

Wireless LAN Data and Voice Communications

WLAN Radio:	Tri-mode IEEE® 802.11a/b/g Note: 802.11a not available in Thailand.
Data Rates Supported:	1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 and 54 Mbps
Operating Channels:	Chan 8-169 (5040 – 5845 MHz) Chan 1-13 (2412-2472 MHz) Chan 14 (2484 MHz) Japan only Actual operating channels/frequencies depend on regulatory rules and certification agency
Security:	WPA2, WEP (40 or 128 bit), TKIP, TLS, TTLS (MS-CHAP), TTLS (MS-CHAP v2), TTLS (CHAP), TTLS-MD5, TTLS-PAP, PEAP-TLS, PEAP (MS-CHAP v2), AES, LEAP
Spreading Technique:	Direct Sequence Spread Spectrum (DSSS) and Orthogonal Frequency Division Multiplexing (OFDM)
Antenna:	Internal for LAN, External for WAN
Voice Communication:	Integrated Voice-over-IP ready (P2P, PBX, PTT), Wi-Fi™-certified, IEEE 802.11a/b/g direct sequence wireless LAN

Wireless PAN Data and Voice Communications

Bluetooth:	Class II, v 1.2
------------	-----------------

Data Capture Specifications

Options:	1D linear, 2D imager
----------	----------------------

Linear 1D Scanner (SE950)

Optical Resolution:	– 0.004 in. minimum element width
Roll:	±35° from vertical
Pitch Angle:	± 65° from normal
Skew Tolerance:	± 50° from normal
Ambient Light:	10,000 candles
Scan Rate:	104 (+/- 12) scans/sec (bi-directional)
Scan Angle:	47° ± 3° default 35° ± 3° reduced

2D Imager Engine (SE 4400) Specifications

Optical Resolution:	640 H x 480 V pixels (gray scale)
Roll:	360°
Pitch Angle:	± 60° from normal
Skew Tolerance:	± 50° from normal
Ambient Light:	Total darkness to 9,000 ft. candles (96,900Lux)
Focal Distance from Front of Engine:	Near: 5 inches Far: 9 inches
Aiming Element (VLD):	650 nm ± 5 nm
Illumination Element (LED):	635 nm ± 20 nm
Field of View:	Horizontal: 32.2°; Vertical: 24.5°

Peripherals and Accessories*

Communication and Charging Cables:	Serial and USB v1.1 charging cables, printer cables, vehicle charging cable, power/charging cable
Battery Chargers:	4-slot battery charger, universal battery charger (requires adapters for MC70 capacity batteries)

Vertical-specific attachments:	Snap-on magnetic stripe reader, snap-on trigger handle, rigid case
Electrical Safety:	Certified to UL / cUL 60950-1, IEC / EN60950-1,
EMI/RFI:	USA: FCC Part 15; Canada: ICES 003 Class B; Europe: EN55022 Class B, EN 55024, EN60601-1-2; Australia: AS/NZS CISPR 22

For countries outside USA, Canada, European Economic Area, Japan or Australia consult your local Motorola representative

*For a complete list of MC70 Peripherals and Accessories, go to www.motorola.com/mc70

Regulatory

Electrical Safety:	Certified to UL / cUL 60950-1, IEC / EN60950-1
Environmental:	RoHS-compliant
WLAN and Bluetooth:	USA: FCC Part 15.247, 15.407; Canada: RSS-210; EU: EN 300 328-1, EN 301 893; Japan: ARIB STD-T33, ARIB STD-T66, ARIB STD-T71; Australia: AS/NZS 4268
Quad Band GSM/EDGE (850, 900, 1800 and 900 bands):	Global: 3GPP TS 51.010, GCF approved module; USA: FCC Part 22, Part 24; Canada: RSS-132, RSS-133; EU: EN301 511; Australia: AS/ACIF S 018, ASTS 001
RF Exposure:	USA: FCC Part 2, FCC OET Bulletin 65 Supplement C; Canada: RSS-102; EU: EN 50360; Australia: AS/NZ 2772.1, ARPANSA
CDMA-EVDO Rev. 0:	Verizon/Sprint/Alltel/Bell Mobility For latest information, contact your local Motorola representative.
EMI/RFI:	North America: FCC Part 15; Canada: ICES 003 Class B; EU: EN55022 Class B, EN 301 489-1, EN 301 489-7, EN 310 489-17, EN 60601-1-2; Australia: AS/NZS CISPR 22
Laser Safety:	IEC Class2/FDA Class II in accordance with IEC60825-1/EN60825-1

Hazardous Location Certifications

Class I, Division II, A,B,C,D (Select Configurations Only)

For countries outside USA, Canada, European Economic Area, Japan or Australia consult your local Motorola representative

Warranty

The MC70 is warranted against defects in workmanship and materials for a period of 12 months from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions.



GSM/EDGE
Network Certified



CDMA-EVDO Rev. 0
Network Certified



A full suite of accessories and 3rd-party peripherals provides convenient charging of MC70 devices and batteries as well as customization for a variety of vertical applications, from trigger handles that increase user comfort to Global Positioning Systems that provide 24-hour, three-dimensional position, velocity and time information to magnetic stripe readers that enable on-the-spot credit card processing and more.



motorola.com

Part number SS-MC70. Printed in USA 12/08. MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. Symbol is a registered trademark of Symbol Technologies, Inc. All other product or service names are the property of their respective owners. ©Motorola, Inc. 2008. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry




MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684