



Zebra® LP/TLP 2844-Z™

Thermal, On-demand Label, Receipt, and Tag Printers

Affordable desktop printers deliver unmatched performance and versatility.

Direct thermal (LP) and thermal transfer (TLP) 2844-Z™ bar code label printers bring powerful performance to applications requiring a space-saving, desktop-size, four-inch printer. Enhanced with a 32-bit microprocessor for fast label-processing throughput, and with print speeds of up to four inches per second, LP/TLP 2844-Z printers provide productivity unparalleled in their class. Their ease of use, including their OpenACCESS™ design and clear media window for simple media loading and monitoring, makes them a foolproof means to increased workplace efficiency.

Flexible Connectivity

With serial, parallel, and USB interfaces, plus an internal or external ZebraNet® PrintServer II option for easy connection to your network, LP/TLP 2844-Z printers meet a variety of connectivity needs. They are fully compatible with Zebra Programming Language (ZPL II®) for seamless integration with other Zebra printers. They also offer ZebraLink™ real-time connectivity and control for centralized printer management. For superb performance for the price, nothing beats the LP/TLP 2844-Z's robust combination of economy, "horsepower," and flexibility.

The LP and TLP 2844-Z integrate easily into a variety of lower-volume printing applications including:

- Shipping/Receiving
- Warehouse shelf labeling and inventory control
- Healthcare specimen labeling and patient tracking
- Retail product marking, shelf labeling, and coupon and receipt printing
- Transportation/Logistics
- E-commerce postage



Connect with it. Count on it.™



LP 2844-Z™ TLP 2844-Z™



Specifications at a Glance*

STANDARD FEATURES

Print methods: Direct thermal (LP) or direct thermal/thermal transfer (TLP)
Construction: ABS double-walled casing
4MB Flash memory (2.75 available to user)
8MB SDRAM (4 MB available to user)
OpenACCESS™ Design
Serial, Parallel & USB interfaces
ZebraLink™ enabled
32 bit RISC processor
Zebra E³® Printhead Energy Control
Scalable fonts
Transmissive and Reflective media sensing
Head-up sensor

Programming Language

ZPL® or ZPL II® Universal language for Zebra printers.
Simplifies label formatting and enables compatibility with other Zebra printers.
ZBI™ - controls and interprets text and data streams from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN or wireless network via email or TCP/IP messaging.

OPERATING CHARACTERISTICS

Environment

Operating Temp. 40° F/5° C to 105° F/41° C
Storage/Transport Environ. -40° F/-40° C to 140° F/60° C

Operating Humidity 10-80% non-condensing
Storage Humidity 10-90% non-condensing

Electrical

Autorangeing external power supply
Input: 100-240 VAC; 50-60 Hz
Output: 20 VDC; 2.5 A

Communication Interface Capabilities

Serial RS232 (DB9)
Centronics® Parallel (36 pin)
USB v 1.1
Internal Ethernet
(with optional ZebraNet PrintServer II)

Agency Approvals

Emissions: FCC Part 15, Subpart B, VCCI, C-Tick
Emissions and Susceptibility: (CE): EN55022 Class-B, EN61000-3-2, EN61000-3-3 and EN55024
Safety: CB Scheme IEC 60950:1991 +A1 +A2 +A3 +A4, UL 60950 and C-UL, IRAM, NOM, AAMI

MEDIA CHARACTERISTICS

Labels

Max. Roll Size: 5"/127 mm O.D. on a 1"/25.4 mm or 1.5"/38 mm I.D. core
Thickness (label & liner): 0.003"/0.08 mm to 0.0075"/0.19 mm

Media Types: Roll-fed or fan-fold, die cut or continuous direct thermal labels with or without black mark, tag stock

For optimum print quality and print engine performance, use Genuine Zebra® supplies.

Ribbon Specifications

NOTE: For optimum print quality and printer performance, use of Zebra genuine ribbon is recommended as well as a notched ribbon core.

Ribbon Width: 1.30 inches (33 mm) to 4.30 inches (110 mm).

Ribbon Capacity: The capacity of the ribbon roll is to be sufficient enough to completely print one roll of media. (1 roll of 5"OD media is the full ribbon capacity)

Core ID: 0.5" (13 mm).

Ribbon OD: 1.36"(35 mm).

Ribbon Length: 244' (74m) using 0.000328" ribbon thickness

Ribbon Type: Wax, wax/resin and resin.

FONTS/GRAPHICS/SYMBOLICS

Fonts and Character Sets

Standard Fonts: 16 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)

Sets: IBM® Code Page 850 international character set

Optional European and Asian fonts

Graphic Features

Supports user defined fonts and graphics – including custom logos

ZPL II drawing commands – including boxes and lines

Bar Code Symbolics

Linear Bar Codes: Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, EAN-14, UPC-A and UPC-E with EAN 2 or 5 digit extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar

2-Dimensional: PDF417, MicroPDF-417, Code 49, Maxicode, Codablock, Datamatrix, and QR code

OPTIONS AND ACCESSORIES

Expanded memory - up to 8 MB Flash with Real Time Clock (for a total of 12MB, 10.75 MB user available)

Dispenser – Label peel and present with label taken sensor.

ZebraNet™ Print Server II – (internal or external via parallel connection only) enables network print capability.

BAR-ONE® software - Windows®-based "WYSIWYG"

European & Asian font sets

Cutter

Liner-free Platen (LP only)

External rewinder

Sturdy, dual-wall, high-density plastic construction ensures LP and TLP 2844-Z printers survive high-traffic environments.

MAXIMUM PRINT AREA

Width: 4.09"/104 mm

Length: 39"/990 mm (with standard memory)

RESOLUTION

203 dpi/8 dots per mm

MAXIMUM PRINT SPEED

4"/102 mm per second

MEMORY

Standard: 4MB Flash (2.75 available to user)

8MB SDRAM (4MB available to user)

Optional: 8 MB Flash (for a total of 12MB with a total of 10.75 MB available to user)

PHYSICAL CHARACTERISTICS

LP 2844-Z

Width: 7.9"/200 mm

Depth: 8.38"/213 mm

Height: 6.7"/170 mm

Weight: 3 lbs./1.3 kg

TLP 2844-Z

Width: 7.9"/200 mm

Depth: 9.75"/248 mm

Height: 6.8"/173 mm

Weight: 3.2 lbs./1.4 kg

MEDIA SPECIFICATIONS

Label and liner width:

1"/25.4 mm to 4.25"/108 mm

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.

HEADQUARTERS

Zebra Technologies International, LLC **PHONE:** +1 847.634.6700 or +1 800.423.0442 **FAX:** +1 847.913.8766
ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

OTHER LOCATIONS

USA: California, Florida, Rhode Island, Wisconsin **EUROPE:** Denmark, France, Germany, Italy, United Kingdom
ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea **LATIN AMERICA:** Argentina, Brazil
MIDDLE EAST: United Arab Emirates



An ISO 9001 registered company
©2003 ZIH Corp.
Printed in U.S.A.
#13087L (1/03) 10M

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.,
160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891
Fax: 888-522-4684