# Zebra® TTP 7000™ Series





specially designed for unattended operation. It's built to work in harsh environments such as heat, cold, and vibration. And with the jam-preventing loop presenter, guillotine cutter, and pull detector, the TTP 7030 provides trouble-free operation. The only maintenance required is to replace the media roll. The TTP 7030 can support 3.15"/80 mm to 4.4"/112 mm media width, plus a wide printing format that provides room for extensive information or graphics, allowing Web or A4 pages to be downscaled into pocket format. When connected via USB interface, the printer is plug-and-play compatible with Windows, or the printer can be addressed directly from the kiosk software in text mode. The TTP 7030 has Flash memory to store large downloaded files like fonts and graphics.

# Zebra Kiosk Receipt Printer Advantages

# Unremitting Reliability to Keep Kiosks Printing

Optimized for tough printing environments where durability, reliability and minimal maintenance and ease of use are critical, Zebra printers maximize uptime and minimize upkeep.

# Easy to Integrate in Kiosk Designs

A small footprint and flexible mounting options make Zebra printers ideal for a variety of applications—whether embedded in a custom kiosk solution or Zebra's Kiosk Print Station.

## **End Benefits**

As part of a self-service kiosk solution, Zebra printers help companies improve service, raise customer satisfaction, increase revenue, and lower operational costs.



## SPECIFICATIONS AT A GLANCE\*

#### **Printer models**

TTP 7030/80, TTP 7030/112

#### Standard features

- Direct thermal receipt printing for 3.15"/80 mm or 4.4"/112 mm width media
- · Looping presenter with pull detector
- · Retract & retain function optional
- · Auto media loading
- · Various media mounting options behind and below give flexibility to kiosk design, up to 9.8"/250 mm dia.
- · media rolls
- · USB connectivity standard
- RS232 serial connectivity optional
- · 203-dpi printing
- · Windows® drivers for plug and play
- · Prints any font, code-page, bar code, and graphics supported by the operating system

#### **Printer specifications**

#### Resolution

203 dpi/8 dots per mm

### Max print width

- 4.1"/104 mm for TTP 7030/112
- 2.8"/72 mm for TTP 7030/80

### Max print length

23.6"/600 mm

### Print speed

3"/75 mm per second

#### Media sensors

Out-of-paper, black mark, paper in presenter, pull detector, and paper low reporting



#### Media characteristics

#### Maximum paper length

23.6"/600 mm

#### Paper width

- 4.4"/112 mm for TTP 7030/112
- 3.1"/80 mm for TTP 7030/80

#### Maximum media roll

9.8"/250 mm

#### Media thickness

0.002"/0.054 mm to 0.005"/0.13 mm

#### Media types

Roll or fanfold paper

#### **Operating characteristics**

#### Environmental

- Operating Temp.: 23° F/- 5° C to 104° F/40° C
- Storage Temp.: 14° F/-10° C to 122° F/50° C
- Operating Humidity: 35% to 75% non-condensing
- · Storage Humidity: 10% to 90% non-condensing excluding the paper

#### **Electrical**

- 24Vdc +/-10%
- 3.1"/80 mm average 2.5A, peak 8.5A
- 4.4"/112 mm— average 3.5A, peak 11A

### **Physical characteristics**

#### TTP 7030/80

• Width: 5.4"/136 mm • Height: 5.6"/141mm • Depth: 5.9"/150 mm • Weight: 5.3 lbs/2.4 kg

### TTP 7030/112

• Width: 6.6"/168 mm • Height: 5.6"/141 mm • Depth: 5.9"/150 mm • Weight: 6.3 lbs/2.9 kg

## Fonts/graphics/symbologies

#### **Bar Codes**

EAN 8 and 13, UPC, Interleaved 2-of-5, ISBN, Code 39, and Code 128

#### Graphics

Logotypes and b&w BMP-files

#### Standard fonts

ATM9 (Monospaced 14.4 cpi), up to 8 fonts can be uploaded

#### **Text attributes**

Underline, bold, italics, reverse print, multiple width and height

#### Comunication and interface capabilities

- · USB, standard
- · Serial RS232 adapter, optional

#### Operating system

Windows® 2000, XP, Server 2003, and OPOS

### Options and accessories

- · Retract & retain function
- 3.1"/80 mm Roll Holder Behind with paper-low sensor, 5.9"/150 mm dia. max
- 3.1"/80 mm Roll Holder Below with paper-low and weekend sensors, 9.8"/250 mm dia. max
- 4.4"/112 mm Roll Holder Behind with paper-low sensor, 5.9"/150 mm dia. max
- 4.4"/112 mm Roll Holder below with paper-low and weekend sensors, 9.8"/250 mm dia. max
- · Paper-low and weekend sensors with v15.7"/400 mm cable
- · Serial Interface Adapter

Specifications subject to change without notice.

©2009 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. All rights reserved. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.



Corporate Headquarters

+1 800 423 0442 inquiry4@zebra.com Asia-Pacific Headquarters

+65 6858 0722 apacchannelmarketing@ zebra.com **EMEA Headquarters** 

+44 (0)1628 556000 mseurope@zebra.com **Latin America Headquarters** 

+1 847 955 2283

inquiry4@zebra.com

Other Locations USA: California, Georgia, Rhode Island, Texas, Wisconsin Europe: France, Germany, Italy, Netherlands, Poland, Spain, Sweden Asia Pacific: Australia, China, India, Japan, South Korea Latin America: Argentina, Brazil, Florida (USA), Mexico Africa/Middle East: Russia, South Africa,

GSA#: GS-35F-0268N P1021844 (11/09)

# **Legacy Technology Services**

# We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert

866-271-9891

# About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

## Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

# **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

## Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

## Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
   Legacy routinely purchases equipment from our clients around the globe.
  - · Data destruction
  - · Hardware disposal
  - Auditing services

### Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

## **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















