

WT41N0

THE NEXT GENERATION IN RUGGED WEARABLE VOICE AND DATA MOBILE COMPUTERS

Easily increase productivity and eliminate errors in your warehouse or distribution center with next generation hands-free voice and data. With the major increase in package volume driven by multi-channel support, demands for the ultimate in customer service, plus increasing regulations for traceability, you need to move more items through your warehouse or distribution center and capture more information about those items than ever before. With the WT41N0 wearable mobile computer on the arms of your workers, you will. Now, workers can keep their hands and eyes on the materials they are handling ' no time is lost handling paper or a handheld mobile device. Add a ring-style scanner worn on a finger and workers can capture 1-D and 2-D bar codes on the fly, able to document the path of that item for full traceability ' and verify that the right items are in the right orders, shipped to the right customers at the right time. The result? Improved customer satisfaction and loyalty. More throughput with the same staff, driving staff utilization up. And less time spent capturing more information on item movement, driving the cost of compliance with traceability regulations down.

SUPERIOR APPLICATION PERFORMANCE

The WT41N0 offers the most power of any device in its class, with a dual core processor and an operating system that can take advantage of both processors 'Windows Embedded Compact 7, Microsoft's latest mobile operating system. Combined with 2GB Flash memory and support for 802.11a/b/g/n wireless LANs, this wearable mobile device delivers the processing power and network throughput required to deliver consistent, lightning-fast application performance and reliability.

POWERFUL VOICE FUNCTIONALITY

A new built-in microphone enables push-to-talk (PTT) calls and voice-directed applications without a headset, helping reduce costs. The ability to simultaneously support multiple audio sources greatly enriches functionality.

ALL THE RIGHT ACCESSORIES

Enrich the functionality of this hands-free solution with our complete accessory family. Our RS507 and RS419 ring scanners give your workers hands-free scanning that boosts productivity in the most scan intensive applications. Our rugged yet highly-cost effective cabled headset provides crystal clear voice in the noisiest and most demanding environments.

READY FOR RUGGED ENVIRONMENTS

Workers can drop, bump or even spill liquid on the WT41N0, yet still expect reliable operation. In addition, the improved touchscreen has been hardened, making it virtually impervious to scratches. And stainless steel connectors combine with an improved coating on the rear cleat to eliminate corrosion and increase durability at accessory attachment points.

Improve the productivity and accuracy of your workers with best-in-class hands-free computing.



FEATURES

Ergonomic hands-free wearable design

Award-winning ergonomic design increases user comfort and productivity

High-performance nextgeneration platform

Best-in-class dual core processor provides the power to run virtually any enterprise application

802.11a/b/g/n WLAN

Easily connects to existing WLAN for fast integration; 802.11n and support for advanced Zebra's WLAN features greatly improves wireless network bandwidth, performance and reliability, while reducing power consumption and improving voice performance

Supports text-only, voiceonly and combination text and voice applications

Eliminates the effort and cost associated with purchasing and supporting multiple hardware systems for different types of applications

Wide temperature range

Designed to operate across a wide temperature range ensures operation in virtually all environments of the warehouse, including -4° F/ -20° C (-22° F/-30° C with freezer pouch)

2.8 in. color QVGA display with backlight

Excellent at-a-glance readability in nearly any lighting condition; optional

To find out how, visit www.zebra.com/wt41n0 or access our global contact directory at www.zebra.com/contact.

hardened touchscreen improves display lifecycle and enables easy data input

SPECIFICATIONS

PHYSICAL AND ENVIRONMENTAL CHARACTERISTICS		USER ENVIRONMENT		
Dimensions	5.7 in. L x 3.7 in. W x 1.0 in. H 142 mm L x 93 mm W x 26 mm H	Operating Temp.	-4° to 122° F/-20° to 50° C -22° to 122° F/-30° to 50° C	
		Storage Temp.	-40° to 158° F/-40° to 70° C	
Weight	Terminal w/ Standard Battery: 11.3 oz. (8.4 oz. + 2.9 oz.) 320.3 g (238.1 g + 82.2 g) Terminal w/ Extended Battery: 13 oz. (8.4 oz. + 4.6 oz.) 369.8 g (238.1 g + 131.7 g) Holder: 2.5 oz./70.9 g (inc. straps and cushion)	Humidity	5% to 95% non-condensing	
		Drop Spec	Multiple drops to concrete: 4 ft./1.2 m across the operating temperature range	
		Tumble Spec	500 one-half meter tumbles at room temperature (1,000 drops)	
Keyboard	23 key alpha-numeric for alpha entry: legacy color-coded alpha entry	Sealing	IP54	
Display Type	Backlit color TFT, touch screen available	Electrostatic Discharge (ESD)	EN61000-4-2 15kV Air, 8kV contact, 8kV indirect	
Display Resolution	QVGA in landscape mode (320 x 240)	PERIPHERALS AND ACCESSORIES		
Power	PowerPrecision Li-Ion batteries Two options: High Capacity 4800 mAh or Standard Capacity 2400 mAh	Cradles	Single-slot USB charging cradle with spare battery well; four-slot Ethernet charging cradle	
		Printers	Supports extensive line of approved printers	
PERFORMANCE	CHARACTERISTICS	Charger	Four-slot battery charger	
Processor	Dual Core OMAP 4 @ 1GHz	Mounts Wrist-mount and hip-mount		
Operating System	Microsoft Windows Embedded Compact CE 7.0		accessories are available	
Memory	512 MB RAM; 2 GB Flash	Other Accessories	RS507/RS419/RS409/RS309	
Application Development	Microsoft IDEs and Zebra SDKs		wearable scanners; RCH51 rugged headset; headset adapters; freezer pouches that extend the operating	
Data Capture Options	Wearable scanners RS507, RS419 , RS409 and RS309 are optional accessories		temperature range	
		REGULATORY		
Communications	USB (Host and Client)	Electrical Safety	Certified to UL60950-1, CSA C22.2 No. 60950-1, EN60950/IEC 60950-	
WIRELESS DATA	A COMMUNICATIONS		1 plus all national deviations	
WLAN	IEEE 802.11a/b/g/n	EMC	FCC Part 15 Subpart B, ICES-003 Class B, EN 61000-3-2, EN 61000- 3-3, CISPR 22 Class B, CISPR 24, EN 301 489-1, EN 301 489-17 FCC Parts 15.247, 15.407, 15.205, 15.207, 15.209, 15.203, EN 300 328, EN301 893, RSS-100, RSS-	
Output Power	100 mW U.S. and international			
Data Rate	802.11a: up to 54 Mbps 802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n up to 72.2 Mbps	RF		

IP54 sealing; tumble tested; and a 4 ft./1.2 m drop specification across entire operating temperature range

Maximizes uptime and ensures dependable operation in demanding environments including cold storage; reduces device replacement costs

Secure WLAN communications

Robust support for the latest security protocols keeps your data safe

Backwards compatibility with all WT4000 accessories

Support for the wearable scanners, rugged headsets, cradles and cables for the WT4000 allows you to cost-effectively upgrade to the very latest in wearable technology

Supports Zebra's best-inclass device management solution

Centrally manage your WT41N0 wearable computers as well as all other Zebra and third party mobile devices in use in your business with Zebra's Mobility Services Platform (MSP)

Supports Zebra Technologies RhoMobile best-in-class operating system-agnostic applications

Integrated support for RhoMobile applications allows easy and costeffective development and deployment of a single application version that runs on practically any device, regardless of operating system or screen size

Antenna	Internal with Diversity	_	210, ARIB STD-66 & 33, ARIB STD-T71, AS/NZS 4268	Push-to-talk (PTT) ready Supports PTT capability, allowing users to reach and
Frequency Range	Country dependent ' typically: 802.11b/g: 2.4 to 2.5 GHz 802.11a: 5.0 GHz		STD-171, AS/N2S 4200	
		VOICE AND AUDIO		be reached at the press of a
WPAN	802.11n: 2.5 and 5.0 GHz Bluetooth 2.1 + EDR	- Audio	AC97 Compatible Codec to play audio over speaker or headset; microphone; simultaneous audio single button, improving collaboration and responsiveness	
RECOMMENDED SERVICES		Push-to-Talk	PTT (client included); wired	_
Service from the Start with Comprehensive Coverage: Complete support program covers normal wear and tear as well as accidental damage and includes technical telephone support, software support and repair.		_	headset support, PTT will support headset and speakerphone mode	
		Voice Directed Picking	TekSpeech Pro Certified; Compatible with 3rd party VDP clients	

Device and Asset Management Services:

device

management services.

Provides fully-managed deployment, optimization and



Part number: SS-WT41N0. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. SYMBOL is a trademark owned by Symbol Technologies, Inc., which is an indirect wholly owned subsidiary of Zebra Technologies Corporation. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES