

CODE READER™ 4405



Features & Benefits

- Lightweight design combines easy-to reach buttons with an unobstructed view of iPhone screen
- Bright, rectangular, blue LED aiming quickly and easily targets and reads all bar codes
- Multiple locking clips hold phone in place, protecting it against damage and minimizing exposure to debris
- Software Development Kit (SDK) assists in creating a custom scanner application
- Single and quad-bay charging station options

Cost-effectively and quickly convert your iPhone® 5 into a mobile bar code reading solution.

Consolidating technologies into one, user-friendly device has perhaps never been more in demand among mobile-driven applications, and the CR4405 sled is leading the way.

Ideal for fast-paced environments such as healthcare and retail, its sleek, ergonomic design features advanced imaging technology for increased productivity and mobile workflow efficiency.

Designed to protect your investment.

The CR4405 iPhone® 5 bar code reading sled is the only one that features replaceable, rechargeable battery cartridges. This makes changing depleted batteries quick and easy, and avoiding workflow interruptions even easier. Its durable, IP54-rated housing withstands harsh environments, and consists of disinfectant ready plastics that stand up to frequent cleaning with rigorous chemicals. The CR4405 delivers superior performance on all 1D, 2D and stacked bar code symbologies, and it includes a software development kit to tailor scanner applications.

For speed, efficiency and versatility, the CR4405 sled for iPhone 5 steps up as the ultimate solution to multiple challenges.



Applications

Healthcare, retail, government, event management

Features at a glance



*Screen and keypad are available via iPhone 5.

CODE READER™ 4405 SPECIFICATIONS

Physical Characteristics

CR4405 Dimensions	6.25" L x 2.8" W x 1.25" D (156 mm L x 75 mm W x 30 mm D)
CR4405 Weight (with battery and phone)	12.0 oz (300.0g)
Charging Station Dimensions	4.6" L x 4.5" W x 2.7" H (117 mm L x 114 mm W x 69 mm H)
Charging Station Weight	5.3 oz (150.0g)

User Environment

Operating Temperature	-20° to 55° C / -4° to 131° F
Storage Temperature	-30° to 65° C / -22° to 150° F
Humidity	5% to 95% non-condensing
Decode Capability	1D: Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, Interleaved 2 of 5, GS1 DataBar (RSS), Hong Kong 2 of 5, Maxtrix 2 of 5, MSI Plessey, Pharmacode, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN Stacked 1D: GS1 Composite (CC-A/CC-B/CC-C), MicroPDF, PDF417 2D: Aztec Code, Data Matrix, Micro QR Code, QR Code, Han Xin Proprietary 2D: GoCode® (Additional License Required) Postal Codes: Australian Post, Intelligent Mail, Japan Post, KIX Code, PLANET, POSTNET, UK Royal Mail
Image Output Options	Formats: JPEG or PGM
Field Selection	High Density or Wide Field
Time Stamp	Interval Logging
Data Editing	JavaScript (Additional License Required) / CodeXML® Rules

Working Ranges

CR4405 Performance

Test Code	Min Inches (mm)	Max Inches (mm)
3 mil Code 39	3.1" (80 mm)	4.0" (102 mm)
7.5 mil Code 39	1.3" (33 mm)	7.2" (182 mm)
10.5 mil GS1 DataBar	0.8" (20 mm)	8.7" (220 mm)
13 mil UPC	1.1" (28 mm)	11.0" (280 mm)
4.2 mil DM	1.9" (48 mm)	4.3" (110 mm)
5 mil DM	1.7" (43 mm)	4.5" (115 mm)
6.3 mil DM	1.3" (33 mm)	5.9" (150 mm)
10 mil DM	0.8" (20 mm)	7.1" (180 mm)
20.8 mil DM	1.1" (28 mm)	13.5" (343 mm)

Note: Working ranges are a combination of both the wide and high density fields. All samples were high quality codes and were read along a physical center line at a 10° angle. Default AGC settings were used. Accuracy= +/- 10%.

Performance Characteristics

Field of View	High Density Field: 30° horizontal by 20° vertical Wide Field: 50° horizontal by 33.5° vertical
Focal Point	Approximately 100 mm
Sensor	CMOS 1.2 Megapixel (1280 x 960) gray scale
Optical Resolution	High Density Field: 960 x 640 Wide Field: 960 x 640
Pitch	± 60° (from front to back)
Skew	± 60° from plane parallel to symbol (side-to-side)
Rotational Tolerance	± 180°
Print Contrast Res.	25% (1D symbologies) or 35% (2D symbologies) absolute dark/light reflectance differential, measured at 650 nm
Target Beam	Single, blue targeting bar
Ambient Light Immunity	Sunlight: Up to 9,000ft-candles/96,890 lux
Shock	Without phone withstands multiple drops of 6' (1.8 Meters) to concrete With phone withstands multiple drops of 4' (1.22 meters) to concrete
Memory Capacity	128MB Flash ROM, 32MB RAM
Communication Interfaces	USB, Wireless Interfaces Supported by iPhone 5
Operational Modes	iPhone App Mode, iPhone Keyboard Mode
Warranty	1 Year; extended service plan available

Accessories

- Lithium-Ion Battery
- Single and quad-bay charging stations



code
ADVANCED BAR CODE READERS

Phone: (801) 495-2200
Web: www.codecorp.com