

POWERSCAN™ RETAIL PBT9500-RT



BUILT TO LAST

With the durability of the renowned industrial PowerScan family, the PowerScan imager is now being introduced into the retail sector with a new series of 'Retail' scanners. The PowerScan PBT9500-RT imager is a cordless scanner featuring *Bluetooth®* wireless technology. The rugged mechanics of the PowerScan Retail series guarantees reliable long-term operation in retail activities. Repeated shocks at the POS checkout or outdoor usage do not inhibit the scanner's performance or reliability, protecting the retailer's investment. The IP65 rating further guarantees protection from damages caused by exposure to moisture.

NOW WITH DIGITAL WATERMARKING

Digital watermarked bar codes include the same Global Trade Item Number (GTIN) data contained in the UPC/EAN symbologies, but repetitively distributes the GTIN data across the entire package without altering the packaging aesthetics.

The PowerScan Retail 9500 series is the first handheld series of scanners on the market capable of reading digital watermarks including Digimarc® Barcodes. This new application significantly reduces time at the checkout. Cashiers can scan items quicker without having to hunt for the bar code or lift bulky items from the trolley.

MOBILITY ENHANCES PRODUCTIVITY

The PowerScan PBT9500-RT Retail series can transmit data to the host through its base station as well as to any commercial or embedded *Bluetooth v2.0* compliant device. Wide radio coverage and the full keypad allow these mobile imagers to be used at the POS checkout as well as for inventory or shelf replenishment activities. When placed in the vertical cradle, the PowerScan Retail imager automatically switches into presentation mode. To coordinate with different POS systems, the imagers are offered in 2 colors: dark gray or white with a silver top cover.



FEATURES

- Outstanding robustness (2.0 m / 6.6 ft drops) and an IP65 sealing rating
- *Bluetooth* wireless technology 3.1 Certified Class 1
- Vertical cradle for presentation mode scanning
- Digital watermarks including Digimarc® Barcodes
- Standard Ethernet
- Snappy omnidirectional reading
- Intuitive aiming system
- In-field replaceable window and cradle contacts
- Datalogic's 3GL™ (3 Green Lights) technology and loud beeper for good-read feedback
- Datalogic's Motionix™ motion-sensing technology
- Ergonomic shape
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Retail
 - Point of Sale Checkout
 - Shelf Replenishment
 - Goods Receiving
 - Inventory
- Healthcare
 - Patient Tracking
- Commercial Services
 - Postal
 - Banks
 - Public Administration
 - Utilities

POWERSCAN™ RETAIL PBT9500-RT



TECHNICAL SPECIFICATIONS

CORDLESS COMMUNICATIONS

| | |
|-------------------------------|---|
| BLUETOOTH WIRELESS TECHNOLOGY | Piconet: Max. Readers per Radio Receiver Using Commercial Dongle: 7; Using Cradle: 4 |
| PROFILES | HID (Human Interface Device); SPP (Serial Port Profile) |
| PROTOCOL | Bluetooth 3.0 Certified Class 1 |
| RADIO FREQUENCY | 2.40 to 2.48 GHz |
| RADIO RANGE (OPEN AIR) | Class 1: Exceeds 90 m/295 ft Range distances are measured using the base station. Range with connection to other Bluetooth peripherals may show different results. |
| SECURITY | Data Encryption; Scanner Authentication |

DECODING CAPABILITY

| | |
|---|---|
| DIGITAL WATERMARKS 1D / LINEAR CODES | Includes Digimarc® Barcodes Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes |
| 2D CODES | Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code |
| POSTAL CODES | Australian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post |
| STACKED CODES | EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites |

ELECTRICAL

| | |
|-----------------------|---|
| BATTERY | Lithium-Ion 2150 mAh Charge Time: External Power: 4 Hours; Host Power: 10 Hours |
| READS PER CHARGE | Continuous Reading: 30,000+ |
| CRADLE INDICATOR LEDS | Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow) |
| CURRENT | Charging (Typical): External Power: 800 mA @ 10 VDC; POT: 500 mA @ 5 VDC |
| OPERATING (TYPICAL) | 150 mA @ 10 VDC |
| INPUT VOLTAGE | External Power: 10-30 VDC; POT: 5 VDC +/- 10% |

ENVIRONMENTAL

| | |
|--------------------------------|--|
| AMBIENT LIGHT | 0 - 100,000 lux |
| DROP RESISTANCE | Cradle: Withstands 50 drops from 1.2 m / 3.9 ft onto a concrete surface PBT9500-RT: Withstands 50 drops from 2.0 m / 6.6 ft onto a concrete surface |
| ESD PROTECTION (AIR DISCHARGE) | 20 kV |
| HUMIDITY (NON-CONDENSING) | 95% |
| PARTICULATE AND WATER SEALING | IP65 |
| TEMPERATURE | Operating: -20 to 50 °C / -4 to 122 °F Battery Charging: 0 to 45 °C / 32 to 113 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F |

INTERFACES

| | |
|------------|---|
| INTERFACES | RS-232; USB COM; USB HID Keyboard; Optional Ethernet |
|------------|---|

PHYSICAL CHARACTERISTICS

| | |
|------------------|--|
| COLORS AVAILABLE | Dark Gray / Black; White / Light Gray |
| DIMENSIONS | Cradle: 22.0 x 10.0 x 11.0 cm / 8.6 x 3.9 x 4.3 in PBT9500-RT: 21.2 x 11.0 x 7.4 cm / 8.3 x 4.3 x 2.9 in PBT9500-RT: 380.0 g / 13.4 oz PBT9500-RT-DK: 414.0 g / 14.6 oz |
| WEIGHT | |

READING PERFORMANCE

| | |
|--------------------------------|---|
| IMAGER SENSOR | 864 x 544 |
| LIGHT SOURCE | Aiming: 630 - 680 nm VLD Illumination: Red LEDs |
| MOTION TOLERANCE | 90 cm / 35 in per second |
| PRINT CONTRAST RATIO (MINIMUM) | 15% |
| READING ANGLE | Pitch: +/- 40°; Roll (Tilt): 360°; Skew (Yaw): +/- 40° |
| READING INDICATORS | Beeper (Adjustable Tone and Volume); Datalogic's 3GL™ (Three Green Lights) technology and loud beeper for good-read feedback; Datalogic 'Green Spot' on the Code, Dual Good Read LEDs |
| RESOLUTION (MAXIMUM) | 1D Codes: 4 mils; 2D Codes: 7.5 mils |

READING RANGES

| | |
|---------------------------------------|---|
| TYPICAL DEPTH OF FIELD | Minimum distance determined by symbol length and scan angle; Printing resolution, contrast, and ambient light dependent. |
| DIGITAL WATERMARKING 1D / 2D CODES | Maximum: 30 cm / 11.8 in 4 mils: 6.0 to 17.0 cm / 2.3 to 6.7 in 13 mils: 4.0 to 45.0 cm / 1.5 to 17.7 in 20 mils: 4.0 to 55.0 cm / 1.5 to 21.6 in 40 mils: 4.0 to 85.0 cm / 1.5 to 33.4 in 10 mils PDF417: 2.0 to 25.0 cm / 0.8 to 9.8 in 7.5 mils Data Matrix: 9.0 to 12.0 cm / 3.5 to 4.7 in 10 mils Data Matrix: 4.0 to 18.0 cm / 1.5 to 7.0 in |

SAFETY & REGULATORY

| | |
|--------------------------|--|
| AGENCY APPROVALS | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| ENVIRONMENTAL COMPLIANCE | Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H. |
| LASER CLASSIFICATION | Caution Laser Radiation - Do not stare into beam CDRH Class II: IEC 60825 Class 2 |
| LED CLASSIFICATION | IEC 62471 Class 1 LED |

UTILITIES

| | |
|----------------------|---|
| DATALOGIC ALADDIN™ | Datalogic Aladdin configuration program is available for download at no charge |
| OPOS / JAVAPOS | JavaPOS Utilities are available for download at no charge; OPOS Utilities are available for download at no charge |
| REMOTE HOST DOWNLOAD | Available on request |

WARRANTY

| | |
|----------|-------------------------|
| WARRANTY | 3-Year Factory Warranty |
|----------|-------------------------|

ACCESSORIES

Base Stations/Chargers



■ BC9030-BT-RT
Vertical Base/Charger



■ BC9180-BT-RT
Multi-Interface/Ethernet
Base/Dual Charger