



General Purpose Corded Handheld Laser Bar Code Reader

The QuickScan reader series is Datalogic Scanning's value line of general purpose handheld data collection products. As an entry level scanner, the QuickScan L scanner provides a simple solution for those who prefer laser scanning technology and need to read bar codes at nominal distances. A wider than usual scan angle provides the ability to read a longer bar code from a shorter distance.

Perfect for use in retail and office environments, its small, lightweight and ergonomic design is comfortable to use during daily operations. The QuickScan L reader has snappy reading performance and is capable of reading a wide range of symbologies including the majority of 1D codes plus GS1 DataBar™ linear codes.

The QuickScan L reader has been designed with durability in mind. One of the most vulnerable features of any scanner is damage to the scan window. When such

incidents happen, the scanner may have to be replaced. The QuickScan L reader was specifically designed so that a replacement window pack can be ordered to replace damaged or scratched windows without having to send the scanner away for repairs. This helps to reduce the total cost of ownership during the life of the scanner and helps to ensure that it is always available for use.

Each QuickScan L reader comes with multiple interfaces which cover the most popular interfaces and includes various packaging options so that it can be ordered as the scanner only or as a kit equipped with a scanner, cable and stand to facilitate hand-free reading options.

Features

- Wider scan angle for longer code reading
- User replaceable scan window
- Multi-interface solution for the most popular interfaces
- Supports GS1 DataBar™ linear codes
- Water and Particulate Sealing Rating: IP42
- Drop resistance to 1.5 m / 4.9 ft
- 20 kV Electrostatic protection (air discharge)



Specifications

DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes
China Post

POSTAL CODES

ELECTRICAL

CURRENT

Operating (Typical): 100 mA @ 5 VDC
Standby/Idle (Typical): < 35 mA
5 VDC +/- 10%

INPUT VOLTAGE

ENVIRONMENTAL

AMBIENT LIGHT

64,575 lux

DROP RESISTANCE

Withstands repeated drops from 1.5 m / 5.0 ft onto a concrete surface

ESD PROTECTION (AIR DISCHARGE)

20 kV

HUMIDITY (NON-CONDENSING)

5 - 95%

PARTICULATE AND WATER SEALING

IP42

TEMPERATURE

Operating: 0 to 50 °C / 32 to 122 °F
Storage/Transport: -40 to 70 °C / -40 to 158 °F

INTERFACES

Keyboard Wedge; RS-232; USB; Multiple Interfaces Available

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE

Black; White

DIMENSIONS

17.0 x 7.1 x 6.6 cm / 6.7 x 2.8 x 2.6 in

WEIGHT

127.6 g / 4.5 oz

READING PERFORMANCE

LIGHT SOURCE

650 nm VLD

PRINT CONTRAST RATIO (MINIMUM)

30%

READ RATE (MAXIMUM)

100 reads/sec.

READING ANGLE

Pitch: +/- 65°; Roll (Tilt): +/- 30°; Skew (Yaw): +/- 60°

READING INDICATORS

Beeper (Adjustable Tone); Good Read LED

RESOLUTION (MAXIMUM)

0.130 mm / 5 mils

READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle.
Printing resolution, contrast, and ambient light dependent.
5 mils: 2.0 to 13.0 cm / 0.8 to 5.1 in
7.5 mils: 1.0 to 20.0 cm / 0.4 to 8.0 in
10 mils: 0.5 to 22.0 cm / 0.2 to 8.6 in
13 mils: 0.5 to 24.5 cm / 0.2 to 9.8 in
20 mils: 3.0 to 27.0 cm / 1.2 to 10.5 in

SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.
The Quick Reference Guide for this product can be referred to for a complete list of certifications.

ENVIRONMENTAL COMPLIANCE

Complies to China RoHS; Complies to EU RoHS

LASER CLASSIFICATION

Caution Laser Radiation - Do not stare into beam; EN 60825-1 Class 2; IEC 60825-1 Class 2

WARRANTY

3-Year Factory Warranty



Miscellaneous

- 11-0318 Replacement Windows, 5-Pack



Mounts/Stands

- STD-QD20-BK Gooseneck Stand, Black
- STD-QD20-WH Gooseneck Stand, White

© 2008 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.
• Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo is a trademark of Datalogic S.p.A. • QuickScan is a registered trademark of Datalogic Scanning Inc.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-QUICKSCANL-EN 20081212

www.scanning.datalogic.com