

IMAGETEAM™ 3800PDF *Hand Held Linear Imager for PDF417*



Now with RSS

Features

PDF Decoding - Fast, accurate, economical PDF reading using an innovative feedback design.

Bright, Sharp and Focused Aiming Line - Easy to aim and scan codes in any lighting condition from darkness to full sunlight, tightly stacked bar code sheets, or small, high resolution labels.

Solid, Rugged Design - No moving parts inside and solid construction outside deliver years of reliable service in demanding work environments.

Modern Design - Attractive styling compliments most existing POS environments, while user comfort is enhanced by the smooth handle curves, soft molded grip area, and comfortable trigger.

Powerful, Flexible Architecture - Connects and interfaces to all major PCs and terminals easily and quickly with Windows® based programming tools or bar code programming menus.

Increased Reading Distances - Easily covers the full range of hand held scanning uses in point of sale and general purpose scanning applications.

Real World Reading Performance - Accommodates printer induced bar space variation, faded labels, short quiet zones, low contrast codes, dot matrix printing, and multipart forms with higher resolution, better optics, and improved decoding algorithms.

5 Year Warranty

The IT3800PDF model delivers fast and accurate reading of PDF417 codes as well as all standard linear symbologies. The specially designed hardware and firmware are optimized for exceptional PDF417 performance in all types of scanning applications. PDF417 reading is accomplished by sweeping the scanner up or down over the code, quickly gathering, decoding, and outputting the data to the host system. The scanner ticks while collecting data, providing instant user feedback on performance. All symbologies are automatically discriminated with no reduction in decoding speed.

The IMAGETEAM™ 3800PDF is a high performance, hand held bar code scanner. The IT3800PDF uses linear imaging technology to set a new standard for hand held scanners by combining a bright, sharp aiming line with high resolution imaging to deliver exceptional reading performance.

Each decoded output scanner has the capability to connect as a keyboard wedge, use the serial port, output non decoded laser compatible signals, or operate in wand emulation mode. The IT3800PDF connects to all popular PCs, Apple MAC, USB, and portable data terminals. A non decoded mode can be used with external wedge decoders and portable terminals or other devices with decoding capability. Standard cables are used to reduce replacement expense.

The IT3800PDF is excellent in hand held scanning applications, such as retail point of sale and in-store inventory. It operates from a tabletop holder in manual trigger mode, or may be placed in an adjustable stand for automated operation. The IT3800PDF can be used indoors or outside in bright sunlight. Typical applications are retail point of sale, in-store inventory, document management, transaction processing of bar coded receipts, payment counter, outdoor sales kiosks, and reading of vehicle registrations.

IMAGETEAM 3800PDF Specifications

Performance

Illumination: 630 NM Visible Red LED
Receiving Device: 3648 element linear imager

PDF417 Bar Codes 3:1 Aspect Ratio

Reading Distance	10 mil	15 mil
Minimum	3 in. 7.6 cm	3 in. 7.6 cm
Maximum	4.5 in. 11.4 cm	5 in. 12.7 cm

Skew Angle: $\pm 55^\circ$
Pitch Angle: $\pm 55^\circ$
Horizontal Velocity: 2 in. (5.1 cm) per second
Minimum Reflectance Difference: 40%
Scan Rate: Programmable to 270 scans per second
Decode Rate: Up to 270 decodes per second

Mechanical/Electrical

Dimensions

Length: 5.3 in. (13.5 cm)
Height: 6 in. (15.2 cm)
Width: 3.1 in. (7.9 cm)
Weight: 6.3 oz. (179.2 g)

Housing: Polycarbonate/ABS blend, UL 94V0

Power Requirements: 5Vdc \pm 10% at scanner

Current Draw:	Scanning	Standby	In-Rush
@270 s/s	275mA	125mA	300mA
@67 s/s	150mA	125mA	300mA

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature

Operating: +32°F to +122°F (0°C to +50°C)
Storage: -4°F to 140°F (-20°C to +60°C)

Humidity: 0 to 95%

Mechanical Shock: Operational after 50 drops from 5 ft. (1.53 m) to concrete

Ambient Illumination: 0 - 70,000 lux

ESD Protection: Functional after 15kV discharge

Vibration: Withstands 5G peak from 20 to 300 Hz

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV

MTBF: per MIL-HDBK-217F Ground Benign exceeds 100,000 hours

Symbologies: PDF417, Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Postal Code, RSS.

Interfaces: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, Apple ADB, USB, TTL Level Serial Wedge, TTL level RS-232, wand emulation mode, and includes (HHLC) non decoded laser compatible output.

Warranty: Five year factory warranty.

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa

Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France

Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com

Offices Serving Latin America

Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com
São Paulo
Tel: +55 11 5016 3454
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2176 0250
lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2004. All rights reserved. Printed in the U.S.A.

Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.