

Product profile

Duratron S

Thermal Transfer Film



- Recommended for outdoor use (up to 6 months)
- Resistant to grease and oil
- Tear resistant
- Available with permanent or removable adhesive
- Excellent print quality for graphics and high resolution barcodes

Intermec's Duratron S product offers reliable performance in challenging tracking applications at an economical price point. This durable label readily endures outdoor exposure to rain, snow, and ultraviolet light for up to six months. With its synthetic face sheet construction, it is ideal for environments where it will encounter exposure to moisture, oils, and grease. Duratron S provides a cost effective solution for labeling applications such as:

- Medical specimens (exposure to moisture or some chemicals)
- Industrial bins
- Horticultural products
- Automotive components
- Outdoor furniture
- Building products
- Drum labels
- Shelf labeling

The Intermec Advantage

- Intermec printers and media are optimized to deliver superior performance when used together. Our rigorous testing and co-engineering ensures maximum print head service life, consistently high print quality, and proven label and tag performance in demanding real-world environments
- The use of Genuine Intermec Media ensures consistent performance through the printer and in the end use application resulting in a solution that can be deployed with confidence in a broad range of customer environments.
- When Genuine Intermec Media is used exclusively with Intermec printers, the Free Printhead Replacement Program lowers the total cost of ownership.

Description

Matte Polypropylene

Physical Attributes Facestock

Caliper: 2.7 – 3.3 (Mils)

Adhesive

Permanent Acrylic

Caliper: 0.63 -0.77 (Mils)

Liner

40# Bleached Super Calendared Kraft

Caliper: 2.25 – 2.75 (Mils)

Ribbon Compatibility

TMX1500

TMX2200

Recommended for Outdoor Use

6 months

Environment

Storage Temperature: 40°F to 80°F

Storage Humidity: 35% to 75%

Shelf Life: 12 months

Minimum Application Temperature: 25°F

Service Temperature: -75° to + 200°F

North America**Corporate Headquarters**

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

**North Latin America
Headquarters Office**

Mexico
Phone: +52 55 52-41-48-00
Fax: +52 55 52-11-81-21

South Latin America**Headquarters Office**

Brazil
Phone: +55 11 5502.6770
Fax: +55 11 5502.6780

**Europe/Middle East &
Africa Headquarters Office**

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific**Headquarters Office**

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW:
00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

**Customer Service
and Support**

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2010 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 612024-01A 03/10

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

