

Product profile

INtact Label

Thermal Transfer Film



- Ideal for cryogenic processing and storage
- Tear resistant
- Excellent print quality for graphics and high resolution barcodes
- Recommended for short term outdoor applications (3-6 months)
- Resistant to grease and oil

Intermec's INtact Label offers excellent performance in a wide range of challenging tracking applications. In addition to surviving cryogenic processing and storage, this durable label readily endures outdoor exposure to rain, snow, and ultraviolet light for 3-6 months. With its synthetic facesheet, it is perfect for challenging environments where it will encounter exposure to moisture, oils, and grease. This label stock is ideally suited for labeling applications such as:

- Cryogenic tracking
- Industrial bins
- Automotive components
- Medical devices
- Medical specimens (exposure to moisture or some chemicals)
- Horticultural products
- Building products
- Drum labels

Intermec Advantage

Intermec printers and media are optimized to deliver superior performance when used together. Our rigorous testing and coengineering ensures consistently high print quality, proven label and tag performance in demanding real-world environments, and maximum print head service life for reduced downtime.

Intermec printers and media are complemented by the industry's only complete line of integrated solutions and services, including rugged mobile computers, RFID systems, and advanced scanning technology. Intermec products and services are used by customers worldwide to improve the productivity, quality and responsiveness of their business operations.

Product Characteristics

Face Stock

Description: Gloss Polypropylene Label

Physical Attributes: Caliper (Mils) 2.6

Adhesive

Description: Acrylic Permanent

Physical Attributes: Caliper (Mils) 0.7

Performance Attributes: Peel Adhesion
(oz/in 90° Stainless Steel) 35 Target

Liner

Description: 40# Supercalendered Kraft

Physical Attributes: Caliper (Mils) 2.5

Ribbon Compatibility

TMX 3000 series

Recommended for Outdoor Use: 3-6 months

Compliance

FDA

Environment

Storage Temperature: 40°F to 80°F

Storage Humidity: 35% to 75%

Shelf Life: 12 months

Minimum Application Temperature: 25°

Service Temperature: -112°F to 200°F

North America**Corporate Headquarters**

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348 2600
Fax: (425) 355 9551

North Latin America**Headquarters Office**

Mexico
Phone: (+52) 55 52 41 48 00
Fax: (+52) 55 52 11 81 21

South Latin America**Headquarters Office**

Brazil
Phone: (+55) 11 3711 6776
Fax: (+55) 11 5502 6780

**Europe, Middle East
& Africa****Headquarters Office**

Reading, United Kingdom
Phone: (+44) 118 923 0800
Fax: (+44) 118 923 0801

Asia Pacific**Headquarters Office**

Singapore
Phone: (+65) 6303 2100
Fax: (+65) 6303 2199

Media Sales

EMEA: (+31) 24 372 3167
USA: (513) 874 5882
<http://intermec.custhelp.com>

Sales

Toll Free NA: (800) 934 3163
Toll in NA: (425) 348 2726
Freephone ROW:
00800 4488 8844

OEM Sales

Phone: (425) 348 2762

**Customer Service
and Support**

Toll Free NA: (800) 755 5505
Toll in NA: (425) 356 1799
EMEA: intermec.custhelp.com

Internet

www.intermec.com

Worldwide Locations

www.intermec.com/locations



Copyright © 2013 Intermec Technologies Corporation.
All rights reserved. Intermec is a registered trademark of
Intermec Technologies Corporation. All other trademarks
are the property of their respective owners.
612266-A 01/13

In a continuing effort to improve our products, Intermec
Technologies Corporation reserves the right to change
specifications and features without prior notice.