

## Product profile



# TMX1500

ThermaMAX Thermal  
Transfer Ribbon

- Transportation and logistics
- Compliance labeling
- Automotive components
- Medical specimens (vials, slides, etc.)
- Lawn and garden equipment
- Building products
- Drum labels
- Valuable asset tracking
- Industrial bins

## Enhanced Wax ThermaMAX Thermal Transfer Ribbon

When paired with compatible labels and tags, Intermec's ThermaMAX TMX1500 produces sharp text and bar codes on a broad range of materials, both papers and films, with durability above many competing wax ribbons. TMX1500 is engineered to provide an economical solution for most general use applications. The ThermaMAX TMX1500 ribbon is ideally suited for materials such as:

- Duratran II Paper Label
- Duratran II Paper Tag
- Duratran II Kimdura Label
- Duratran II Syntran
- Duratran II Synthetic Tag
- Duratran II Valeron Tag

### Better Together

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting
- When Intermec media is used exclusively with Intermec printers, the Free Printhead Replacement Program offers significant cost savings

## Product Characteristics:

### Ribbon Construction

**Total Ribbon Thickness:** 7.2 to 8.8 µm  
**Ribbon Film Thickness:** 4.4 to 5.2 µm  
**Ribbon Film Type:** Polyethylene terephthalate

### Properties

**Ink Color:** Black  
**Ink Pigment:** Carbon black  
**Image Density (4ips/4420):** 1.70 min.  
**Flaking Resistance:** No flaking  
**Film Break Strength (MD):** 29 kg/mm<sup>2</sup> min.  
**Film Shrinkage:** 3% max. at 150° C/30 min.

### Performance Attributes

**Scratch (2ips/Kimdura):** B at 100 cycles/2.95# arm  
**Ambient Operating Temperature and RH:** 5 to 35°C, 5 to 70% RH  
**Print Quality (4ips/PM4i):** ANSI A on 10 mil ladder

### Printers

**Intermec labels and tags are engineered to produce optimum print quality when used in Intermec printers with the proper ribbon/material combination.**

### Storage Conditions

**Temperature:** 41°F to 95°F OR 5°C to 35°C  
**Relative Humidity:** 20 to 85% RH  
**Shelf Life:** 12 months

### North America

**Corporate Headquarters**  
6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

### Intermec Deutschland

Burgunder Strasse 31  
40549 Düsseldorf  
Germany  
Phone: 0049 211 53601-0  
Fax: 0049 211 53601-50  
Email: germany.marketing@intermec.com  
Web: www.intermec.de

### South America & Mexico

**Headquarters Office**  
Newport Beach, California  
Phone: (949) 955-0785  
Fax: (949) 756-8782

### Europe/Middle East & Africa

**Headquarters Office**  
Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

### Asia Pacific

**Headquarters Office**  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

### Internet

www.intermec.com  
Worldwide Locations:  
www.intermec.com/locations

### Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW: 00 800 4488 8844  
Toll ROW: +44 134 435 0296

### OEM Sales

Phone: (425) 348-2762

### Media Sales

Phone: (513) 874-5882

### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611841-A 09/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

