



MC3000 Family



Windows CE available on all MC3000 form factors

FEATURES

Light, ergonomic design

Reduces user fatigue for higher productivity in scan-intensive applications

Brick or gun form factors

Comfortable use in intensive or non-intensive scan environments

Audio and visual scanning feedback

Provides visual in addition to audio feedback without having to reorient the device. Visual feedback only on gun.

Brick versions with available rotating laser

Adjust the scanning positions left, right and front for maximum comfort and productivity

320 x 320 resolution color/mono touch display (with backlight)

30% higher resolution than 1/4 VGA allows easy viewing in many environments

Wireless 802.11a/b/g LAN connectivity

Provides real-time wireless data exchange for maximum productivity

Bluetooth option

Enables use of wireless connection to a range of devices

Capture, move and manage data in real time for real business value

The MC3000 mobile computers from Motorola are rugged mobile computers ideal for scan-intensive environments that require high-quality data capture throughout the enterprise. Their superior ergonomic design and balance help to facilitate faster decision making and increased workforce satisfaction inside the retail store, on the loading dock or on a delivery route.

Unprecedented flexibility, performance and power

A variety of feature options, including: color touch display; batch or wireless communications: brick or gun form factor; Bluetooth voice and audio capability; three keypad options; and the ability to capture images, scan bar codes, or read DPM marks, allowing you to meet your customer, employee and IT needs. Each MC3000 mobile computer is based on a high-performance mobile Intel XScale PXA270 processor supporting up to 128MB RAM, which helps you gain significant business value by ensuring maximum user productivity.

The Microsoft Windows CE and Windows Mobile operating systems offer familiar interfaces and the power of Web-based applications for greater usability and employee satisfaction.

Reliable performance in variable conditions

The MC3000s' rugged design and IP54-rated sealing ensure continued use and uptime by protecting against dust, moisture and extreme

temperatures. And, whether working inside or out, the MC3000s have a drop spec of four feet to concrete across a wide temperature range, reducing equipment and maintenance costs.

Unlock the value of your information with Microsoft Windows CE or Windows Mobile

Bringing the next generation of mobile computing to your business, Motorola's MC3000s are built on the Windows CE or Windows Mobile operating systems. With real-time processing, faster performance, rich multimedia and Web browsing capabilities, your enterprise can become truly mobile with interoperability between personal computers, servers, Web services and devices. Motorola's enterprise mobility solutions go beyond mobile devices and wireless connectivity to ensure that every aspect of your mobility solution works seamlessly and at maximum efficiency.

Complete your solution with Motorola Global Services

Even the most rugged products require a maintenance plan and support strategy. That's why Motorola has designed comprehensive set of services that cover every aspect of the MC3000s — helping to ensure our customers derive full value from their investment.

For more information, access our global contact directory at www.motorola.com/customersupport.jsp or visit us on the web at www.motorola.com/mc3000.

SPECIFICATION SHEET

MC3000 Family

Drop, Tumble and Sealing

Meets and exceeds applicable MIL-STD and IEC specs for drop, tumble and sealing

IP54-rated sealing

Protects against water and dust for reliable performance in rough environmental conditions

Intel XScale PXA270 processor and Microsoft Windows CE or Windows Mobile operating systems

Delivers high-speed CPU performance through familiar interfaces with wide software application support

Device management with Mobility Services Platform (MSP)

Enables real-time monitoring of critical mobile computer and wireless infrastructure parameters

MC3000 Series Specifications

Physical Characteristics

| | |
|-----------------------------|---|
| Dimensions | |
| Brick/Imager Configuration: | 7.43 in. L x 3.18 in. W x 1.76 in. D (188 mm x 80.8 mm x 44.7 mm) At grip: 2.40 in. W x 1.43 in. D (61 mm x 36.3 mm) |
| Brick/Laser Configuration: | 8.33 in. L x 3.18 in. W x 1.57 in. D (211.6 mm x 80.8 mm x 39.9 mm) At grip: 2.40 in. W x 1.10 in. D (61 mm x 27.9 mm) |
| Gun Configurations: | 193 L x 80.8 W x 166H mm |
| Weight | |
| Brick/Laser config.: | 13.4 oz. (379 gm) (with WLAN) |
| Brick/Imager config.: | 15.1 oz. (428 gm) (with WLAN) |
| Gun Configurations | 18.59 oz. (527 gm) (19.6 oz./555 gm with Bluetooth) |

Performance Characteristics

| | Monochrome Display Configuration | Color Display Configuration |
|-----------------------|---|--|
| Display Res.: | 320 x 320 | 320 x 320 |
| Operating System: | MC3090: Microsoft Windows CE 5.0 | MC3090: Microsoft Windows CE 5.0 or Windows Mobile 6.1 |
| App Dev.: | Motorola SDK | Motorola SDK |
| Environment: | Microsoft Windows CE SDK | Microsoft Windows CE SDK or Windows Mobile SDK |
| Processor: | IntelXScale PXA270 @312MHz | IntelXScale PXA270 @520MHz |
| Memory: RAM/Flash | 32MB/64MB | 64MB/64MB or 128MB/64MB or 128MB/1GB* |
| Data Capture Options: | 1D Laser: reads 1D bar codes 2D Imager: reads 1D and 2D bar codes omni-directionally DPM Imager: reads data matrix marks, applied by dot peening, laser etching, molding, stamping or casting methods to multiple substrates including metal, plastic, or glass | |
| Secure Digital Slot: | User accessible (located under battery)– approved for memory expansion only | |
| Communications: | RS232, USB (Host and Client) | |
| Power: | Brick/Laser Config. 2,600 mAh @ 3.7Vdc Brick/Imager Config. 4,400 mAh @ 3.7Vdc Gun Configurations 4,400 mAh @ 3.7Vdc | |

Wireless Data Communications

| | |
|-------|--|
| WLAN: | Motorola Spectrum24, 802.11a, 802.11b, 802.11g; note: 802.11a not available in Thailand. |
|-------|--|

*128MB/1GB is available on Windows Mobile only.

| | |
|-----------------------|---|
| Output Power: | 100 mW U.S. and international |
| Data Rate: | 802.11b – 11 MB per second 802.11g – 54 MB per second 802.11a – 54 MB per second |
| Antenna : | Internal |
| Frequency Range: | Country-dependent; typically 2.4 to 2.5 GHz for 802.11b/g and 5.15 to 5.825 GHz for 802.11a |
| Bluetooth: | Theatre dependent |
| VOIP-ready (Class 2): | Optional (theatre dependent) |

User Environment

| | |
|--------------------------------|--|
| Operating Temperature: | Monochrome: -4° to 122°F (-20° to 50°C) Color: 14° to 122°F (-10° to 50°C) |
| Storage Temp: | -22° to 160°F (-30° to 70°C) |
| Batt. Charging Temp: | 32° to -40°F (0° to -40°C) |
| Humidity: | 5% to 95% non-condensing |
| Drop Spec: | Multiple 4-foot (1.2-m) drops to concrete across operating temperature range; Meets and Exceeds MIL-STD 810G |
| Tumble Spec: | 500 one-half meter tumbles at room temperature (1,000 drops) |
| Sealing: | IP54 Category 2 |
| Electrostatic Discharge (ESD): | +/-15kVDC air discharge +/-8kVDC direct discharge +/-8kVDC indirect discharge |

Peripherals and Accessories

| | |
|--------------------|--|
| Cradles: | Single-slot USB/RS232 charging cradle with spare battery well |
| Chargers: | Four-slot battery charger Adaptor for universal battery charger |
| Printers: | Support Motorola approved printers |
| Other Accessories: | Holsters, charging cables, magnetic strip reader |

Regulatory

| | |
|-------------------------|--|
| Electrical Safety: | Certified to UL60950, CSA C22.2No. 60950, EN60950/IEC 950 |
| EMI/RFI Radio Versions: | North America: FCC Part 2 (SAR), FCC Part 15, RSS210 Class B, EN 301 489-1, 489-17 |
| EMI/RFI Batch Versions: | EU: EN55022 Class B EN55024 Japan: CISPR 22, Class B Australia: AS3548 North America: FCC Part 15, ICES 003 Class B |
| Laser Safety: | IEC Class 2/FDA Class II in accordance with IEC60825-1/EN60825-1 |

EN410 CE



MOTOROLA

motorola.com



Part number SS-MC3000. Printed in USA 09/09. MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. Symbol is a registered trademark of Symbol Technologies, Inc. All other product or service names are the property of their respective owners. ©Motorola, Inc. 2009. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.